

Zebra® Kiosk Print Station



A low-cost kiosk solution

Zebra's Kiosk Print Station makes it easy and affordable to bring the benefits of self-service – such as improved sales, customer satisfaction and reduced costs – to your business. The Kiosk Print Station is an accessory that accommodates Zebra's TTP 2000 or TTP 2100 kiosk printer, a roll of Zebra media and a mount for a touch-screen terminal to form a complete, economical alternative to expensive custom kiosks. Simply add your interface and software to complete the solution.

- Quick and easy to integrate – integrates all the kiosk print components into an easy-to-install device that can be wall- or pole-mounted
- Cost-effective – the print station's low cost results in rapid ROI, so even smaller retailers can reap the benefits of self-service kiosks
- Flexible media options – the Zebra Kiosk Print Station supports up to 152mm O.D. media with a 25.4mm core, and widths of 58 to 82.5mm
- Durable and secure – the sturdy lockable metal enclosure securely holds the printer and media. The touch screen is securely fastened to the unit, protecting all components from tampering and tough retail environments
- Trouble-free servicing – the clamshell enclosure opens completely to provide easy access for quick media changes and service
- Unattended printing – the print station accommodates a printer with looping presenter which eliminates paper jamming

Key features:

- A unique ready-to-ship solution
- Installs anywhere: wall- or pole-mountable
- Accommodates a reliable Zebra TTP 2000 or TTP 2100 kiosk printer

Ideal for tickets, receipts, vouchers and information for:

- Retail
- Hospitality
- Healthcare
- Public service
- Public transport
- Parking

NOTE: Printer, accessories and media sold separately from Kiosk Print Station.

Specifications at a glance*

Zebra Kiosk Print Station



Standard features

- All-in-one cost-effective solution for unattended self-serve applications
- Innovative design integrates kiosk hardware components
- Locking enclosure secures printer and media
- Ultra-compact design and pole- or wall-mount saves floor space
- Robust, heavy-duty metal frame with sturdy plastic enclosure
- Supports 152mm (6") media roll in various widths

Peripherals and accessories

- Kiosk computers with VESA 75/100mm Standard mounting

Supported printers

- Zebra TTP 2010™ serial kiosk receipt printer
- Zebra TTP 2030™ USB kiosk receipt printer
- Zebra TTP 2110™ serial kiosk printer
- Zebra TTP 2130™ USB kiosk printer

Supported print features

- Zebra patented looping presenter feature
- Paper low sensor (optional)

Accessories

- Integrated printer power supply
- AC power cord
- USB or serial communication cable
- Paper guide: 51mm (2"), 58mm (2.3") , 60mm (2.4"), 80mm (3.15"), 82.5mm (3.25")

Media options

Supported media

- Widths: 51mm (2"), 58mm (2.3"), 60mm (2.4"), 80mm (3.15"), 82.5mm (3.25")
- Up to 152mm (6") media roll
- 25mm (1") media core
- 8000D 58mm (2.3") receipt media
- 8000D 80mm (3.15") receipt media

Mounting options

- Zebra Kiosk Print Station: pole- or wall-mount
- Third-party kiosk computer: Conforms to the VESA 75/100mm Standard

Environmental

- European RoHS-compliant
- For indoor use only

Physical characteristics

- Width: 462mm (18.2")
- Height: 411mm (16.2")
- Depth: 216mm (8.5")
- Weight: 6.1kg (13.4lbs)
- Weight with printer, 152mm (6") roll of media, printer power supply (excludes computer and computer power supply): 9.3kg (20.4lbs)

Warranty

- One-year limited

NOTE: Refer to the Zebra kiosk price list for additional information, part numbers and pricing on Zebra kiosk printers and supporting products.

Zebra Kiosk Printers TTP 2000 and TTP 2100

TTP 2000 standard features

- Direct-thermal receipt/voucher printing
- Looping presenter with pull detector
- Full- or partial-width guillotine
- Auto media loading
- USB or RS-232 serial connectivity
- Windows® drivers for plug-and-play and direct addressing with ESC commands

Printer models

- TTP 2010 or TTP 2030

TTP 2100 standard features

- Direct-thermal ticket printing
- Auto ticket loading
- Various media mounting options
- USB or RS-232 serial connectivity
- Windows drivers for plug-and-play
- Variable ticket widths

Printer models

- TTP 2110 or TTP 2130

Printer specifications

Resolution

- 8 dots/mm (203dpi)

Maximum print area

- Width: 72mm (2.8") TTP 2000
80mm (3.15") for ATB1 size (TTP 2100)
54mm (2.13") for credit-card size (TTP 2100)
- Length: 70mm (2.76") to 600mm (23.6")

Maximum print speed

- 152mm (6") per second

Media specifications

- Paper widths TTP 2000: 58mm (2.28"), 60mm (2.36"), 80mm (3.15") and 82.5mm (3.25")
- Paper widths TTP 2100: 54mm (2.13") to 82.5mm (3.25")
- Maximum external diameter of media roll for Kiosk Print Station: 152mm (6")
- Minimum diameter of media core: 25mm (1")
- Media thickness TTP 2000: 0.054mm (0.002") to 0.11mm (0.004")
- Media thickness TTP 2100: 0.11mm (0.004") to 0.26mm (0.01") for 54mm (2.13") wide media, 0.11mm (0.004") to 0.19mm (0.007") for 82.5mm (3.25") wide media
- Media type: Roll-fed

Operating characteristics

TTP 2000

Environmental

- Operating temp: -10°C (14°F) to 50°C (122°F)
- Operating humidity: 10% to 95% RH non-condensing

Electrical

- 24VDC +/-5%, average of 2A when printing (85mA idle)

TTP 2100

Environmental

- Operating temp: 0°C (32°F) to 50°C (122°F)
- Storage temp: -10°C (14°F) to 50°C (122°F)
- Operating humidity: 35% to 75% RH non-condensing
- Storage humidity: 10% to 90% RH non-condensing excluding paper

Electrical

- 24VDC +/-5%, average 2A, peak 6A

Physical characteristics

- Width: 105mm (4.1")
- Height: 65mm (2.6")
- Depth: 145mm (5.7")
- Weight: 1.1kg (2.4lb) TTP 2000, 1.4kg (3.1lb) TTP 2100

Options

- Paper-low sensor with 300mm cable

*Specifications subject to change without notice.

©2009 ZIH Corp. All product names and numbers are Zebra trademarks, and Zebra and representation of Zebra Head are registered trademarks of ZIH Corp. All rights reserved. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners.



Zebra Technologies – EMEA Headquarters & Sales Office

Zebra Technologies Europe Limited, Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5XF, United Kingdom

Telephone: +44 (0)1628 556000 Fax: +44 (0)1628 556001 E-mail: mseurope@zebra.com Web: www.zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East & Africa: Dubai, South Africa